

## BEST AVAILABLE COPY

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
20 February 2003 (20.02.2003)

PCT

(10) International Publication Number  
WO 03/014485 A1(51) International Patent Classification<sup>7</sup>: E03F 7/00

(72) Inventors; and

(21) International Application Number: PCT/KR01/01995

(75) Inventors/Applicants (for US only): CHIN, Woo, Seok [KR/KR]; 301-1403 Daewoo Yeolmae Apt., 874 Zaejock-dong, Yusong-gu, Taejeon 302-782 (KR). KWON, Jae, Wook [KR/KR]; 2-805 Kyongnam Apt., 1-8 Banpo-dong, Seocho-gu, Seoul 137-040 (KR). LEE, Dai, Gil [KR/KR]; 107-302 Hanwoll Apt., 162-1 Shinsung-dong, Yusong-gu, Taejeon 305-345 (KR).

(22) International Filing Date:  
21 November 2001 (21.11.2001)

(25) Filing Language: English

(26) Publication Language: English

(74) Agent: JEON, Young, Il; 4202, Trade Tower, World Trade Center, Kangnam-kn, Seoul 135-729 (KR).


(30) Priority Data:  
2001/47684 8 August 2001 (08.08.2001) KR

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(71) Applicant (for all designated States except US): KOREA  
ADVANCED INSTITUTE OF SCIENCE AND TECHNOLOGY [KR/KR]; 373-1, Koo-sung-dong, Yusong-gu,  
Taejeon 305-701 (KR).(71) Applicant and  
(72) Inventor: YOO, Ae, Kwon [KR/KR]; 1802-115, LG  
Village, Sungbok-ri, Suji-up, Youngin-si, Kyonggi-do  
449-840 (KR).(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: REINFORCING ELEMENT OF UNDERGROUND PIPE, AND TRENCHLESS REPAIRING AND REINFORCING METHOD USING THE SAME



(57) Abstract: The present invention relates to a method for repairing and reinforcing an underground pipe. The method of the present invention comprises the steps of inserting an inner mold (20) made of flexible material through the interior of a reinforcing element (10) including a fiber preform (13) surrounded by impermeable inner and outer tubes (11, 12) made of the flexible material and combining the inner mold (20) with the reinforcing element (10); positioning a combined element, which includes the reinforcing element (10) and the inner mold (20), into the underground pipe (30) to be repaired and reinforced; injecting and expanding the inner mold (20) with and by high temperature fluid, and brining the reinforcing element (10) into close contact with an inner wall of the underground pipe (30); injecting the reinforcing element (10) with thermosetting resin; and removing the inner mold (20) after the thermosetting resin has been cured. According to the method of the present invention, there are advantages in that simplification of the processes and reduction of incidental expenses can be obtained since it is not necessary to fasten the cover for injecting the resin and air.